

NEW NILFISK EXTREME - A WORLD OF FEATURES



NILFISK[®] EXTREME

- EXTREME DUST PICK-UP
- ALLERGY FILTRATION
- EXTREMELY SILENT
- 5 YEARS GUARANTEE

NEW NILFISK EXTREME - A WORLD OF FEATURES



EXTREME DUST PICK-UP



ALLERGY FILTRATION



EXTREMELY SILENT



5 YEARS GUARANTEE

FOR THOSE WHO QUITE SIMPLY WANT THE BEST

Nilfisk values are durability, efficiency, functionality and uniqueness of design. Nadya Arnaout from Designworks/USA has designed the new Nilfisk Extreme series to be durable, while at the same time making cleaning easy and ergonomically efficient.

The top model features remote control, ergonomic handle and telescopic tube, exclusive accessories on-board and unique floor nozzles. Plus a 2100W motor and a HEPA filter. No wonder it's called Extreme.



Model	X300	X200	X150	X100
COLOUR	Champagne metallic	Ice blue metallic	Star silver metallic	Coral red
PERFORMANCE:				
RATED POWER/MAX. POWER (W, IEC 335)	1800/2100	1700/2000	1700/2000	1400/1700
SUCTION POWER MOTOR/END OF TUBE (W, IEC 312)	500/400	500/400	500/400	500/300
DUST PICK-UP (% , IEC 312)	78	78	78	76
AIRFLOW WITH HOSE AND TUBE (L/SEC, IEC 312)	40	40	40	38
MAX. VACUUM (KPA)	25	25	25	23
SOUND PRESSURE LEVEL AT 1.5M W/NOZZLE (DB(A) ISO 11203)	54	54	54	54
SOUND POWER LEVEL W/NOZZLE (DB(A) IEC 704-2-1)	70	70	70	70
CONTROLS AND INDICATORS:				
REMOTE CONTROL/VARIABLE SPEED CONTROL	x/-	-/x	-/x	-/-
CABLE REWIND	x	x	x	x
FILTER FULL/BAG FULL INDICATOR	x/x	x/x	x/x	-/x
ABBS (ANTI BAG BURSTING SYSTEM)	x	x	x	-
EWS (EARLY WARNING SYSTEM)	x	x	x	-
FILTERS AND DUST BAG:				
EXHAUST FILTER AREA (CM ²)	HEPA 14/3700	HEPA 14/3700	HEPA 14/3700	HEPA 14/3700
ACTIVE AIR FRESHER FILTER/NILFISK DEODORANT	x/-	-/x	-/-	-/-
DUST BAG CAPACITY (L, OLD/NEW STANDARD)	6.5/3.2	6.5/3.2	6.5/3.2	6.5/3.2
TUBE AND NOZZLES:				
TELESCOPIC TUBE	ALUMINIUM	ALUMINIUM	ALUMINIUM	CHROME
TURBO NOZZLE/HARD FLOOR NOZZLE	x/x	-/x	-/-	-/-
COMBI NOZZLE DELUXE/STANDARD	x/-	x/-	x/-	x/-
OUTLET FOR ELECTRO NOZZLE	x	-	-	-
EASE OF USE:				
ON-BOARD ACCESSORIES	3	3	3	3
PARKING/STOP AND GO PARKING	x/x	x/x	x/x	x/-
SOFT HANDLE/CLICK CONNECTIONS NOZZLE, TUBE	x/x	x/x	x/x	x/x
RADIUS OF OPERATION/CABLE LENGTH (M)	12.2/9	12.2/9	12.2/9	10.2/7
LENGTH X WIDTH X HEIGHT (CM)	39.7x32.3x34.5	39.7x32.3x34.5	39.7x32.3x34.5	39.7x32.3x34.5
WEIGHT MACHINE ONLY (KG)				